

## **HAMMOCKS AT CAPE HAZE**

### **ARCHITECTURAL STANDARD**

#### **GARAGE DOORS VILLAS**

#### **APPROVED GARAGE DOORS: 8'0 X 8'0 AND 8'0 X 16'0**

The above-sized 281 series "Promark" Builder embossed, raised-panel, steel sectional door(s) as manufactured by the Overhead Door Corporation. Door standard features to include the following: Sections are 1 7/8" thick and are embossed from roll-formed hot dipped galvanized steel. Sections are coated on both sides with baked-on gray/white polyester prime coat or white/white finish on exterior only. The bottom section includes a retainer bar with a full length gray PVC bulb-shaped weatherseal.

The above (8'0 x 8'0) doors will include louvered bottom sections. The open area within the louvers for single wide doors is: 247.68 SQ. IN.

Windloaded to The Florida Building Code (130mph) 16'=50psf/8'=46.8psf

#### **Exterior Color – Formula Attached**

- Unit Owner must submit an Architectural Review Committee Request Form and have it approved prior to installing door
- Upon completion of door installation, the unit owner must notify the Hammocks Office Manager and have the door installation inspected

Store: SCOTT PAINT  
Store: 2 VENICE Time: 12:34:57  
Can # 1 of 1 Date: 05/16/2013  
Base ID: WHITE  
Job ID: 0 Size: 1 GALLON  
Color Code/Description:  
HAMMOCKS / BLDGS A GARAGE  
DOORS / ICI 44YY 70/110 / WHITE  
Product Description:

420

Formula:

C-25

I-2


B-5

Rev. Date: 05/16/2013

CUSTOM COLOR NOT  
RETURNABLE



420





## Overhead Door Company Of Sarasota

Corporate Offices  
1249 Stringfield Ave.  
Sarasota, FL 34237  
Telephone: (941) 955-8343  
Fax: (941) 365-1179

Branch Office  
1249 Stringfield Ave.  
Sarasota, FL 34237  
Telephone: (941) 953-5570  
Fax: (941) 365-1179

The Genuine. The Original.



Proposal #: 1-10465

DATE: 10/26/2006

### SUBMITTED TO:

Manhattan Construction  
204 South Hoover Blvd.; Ste. 112  
Tampa, FL 33609

ATTN: Sergio Virto / Bart Amy

### Job Name

Hammocks at Cape Haze

### Job Location

Cape Haze / Englewood

### Job Phone

813-781-2974 (Sergio cell)

### Phone Number

813-675-1960

### Fax Number

813-675-1968

ITEM #	QTY	SERIES	DOOR WIDTH	DOOR HEIGHT	OPENING WIDTH	OPENING HEIGHT	OPERATION	HEAD ROOM	
1	1	281	16	8	16	8	Electric	Standard 14"	
2	1	281	8	8	8	8	Electric	Standard 14"	

### FURNISH AND INSTALL:

The above-sized 281 series "Promark" Builder embossed, raised-panel, steel sectional door(s) as manufactured by the Overhead Door Corporation. Door standard features to include the following: Sections are 1 7/8" thick and are embossed from roll-formed hot dipped galvanized steel. Sections are coated on both sides with baked-on gray/white polyester prime coat or white/white finish on exterior only. The bottom section includes a retainer bar with a full length gray PVC bulb-shaped weatherseal.

- The above (8'0" x 8'0") doors will include louvered bottom sections. The open area within the louvers for the single wide doors is: 247.68 SQ IN.

PRICE FOR THE LOUVERS TO BE ADDED-----

### PROPOSAL TO INCLUDE THE FOLLOWING:

- Operation to be by a model 496 operator featuring 1/3 horse power, (1) single channel transmitter, single light, all chain drive. Photo cell safety system included with unit. Code Dodger rolling code technology standard.

- Operation to be by a model 696 operator featuring 1/2 horse power, (2) single channel transmitters, single light, all chain drive. Photo cell safety system included with unit. Code Dodger rolling code technology standard.

- Windloaded to The Florida Building Code. (130 mph)16'=50psf/8'=46.8psf
- Running of 110 VAC & low voltage wires (wall-button and photocell) will be by others.
- Doors to be installed in opening prepared by others. (2" x 6" PT wood jambs)
- Allow 2-3 weeks for delivery.
- Circle & initial options requested.
- Please sign proposal and return by fax to expedite order.

06

8x8 Louvers  
37/55

June 07

16x8

281

50/75

Page 1 of 2 (Continued on next page ...)

8x8

281

37/55